

COLOREDCRETE

PRODUCT DATA SHEET

Color Hardener

Superior Dry Shake

Streak Free
High Compression Strength
Hard Wearing
Smooth
None Fading
Uniform Color

TECHNICAL DATA:

PERFORMANCE PROPERTIES:

Coloredcrete Color Hardener is inert, lightfast, double milled, element resistant, and free from any fillers or extenders.

WARRANTY LIMITS:

SHELF LIFE:

When Coloredcrete Color Hardener is stored under normal conditions, in a dry/moisture free environment, a shelf life of at least 12 months from the manufactured date will be obtained. The first in/first out method should be observed.

ANTIQUING:

When imprinting with texture mats, antiquing of the surface can be achieved by using Coloredcrete Antiquing Release Agent. After the Coloredcrete Color Hardener has been fully applied, immediately before placing the mats on the concrete, the Release Agent should be broadcast on the surface at a rate of 10 kgs per 90 - 100 square meters. Colouredcrete Antiquing Release Agent forms a release barrier between the texture mat and color hardener. When the texture mat is impressed into the surface, thus leaves grout lines and stone indentations with the color of the antiquing color Release Agent. After the concrete has achieved it's initial set, in hot climates as soon as the next day and in cold climates as long as ten days, the Release Agent may be removed by pressure rinsing with a high power pressure cleaner, or a soap and water solution, and scrubbed with a broom or by brush. Care should be taken not to remove all the release agent from the concrete, especially from grout lines and deeper indentations. To protect and help cure the concrete two coats of ColoredCrete High Gloss Clear Sealer are recommended.

COLOREDCRETE

Color Hardener

Superior Dry Shake

TECHNICAL DATA:**PERFORMANCE PROPERTIES:**

Coloredcrete Color Hardener is inert, lightfast, double milled, element resistant, and free from any fillers or extenders.

WARRANTY LIMITS:**SHELF LIFE:**

When Coloredcrete Color Hardener is stored under normal conditions, in a dry/moisture free environment, a shelf life of at least 12 months from the manufactured date will be obtained. The first in/first out method should be observed.

ANTIQUING:

When imprinting with texture mats, antiquing of the surface can be achieved by using Coloredcrete Antiquing Release Agent. After the Coloredcrete Color Hardener has been fully applied, immediately before placing the mats on the concrete, the Release Agent should be broadcast on the surface at a rate of 10 kgs per 90 - 100 square meters. Colouredcrete Antiquing Release Agent forms a release barrier between the texture mat and color hardener.

When the texture mat is impressed into the surface, thus leaves grout lines and stone indentations with the color of the antiquing color Release Agent. After the concrete has achieved it's initial set, in hot climates as soon as the next day and in cold climates as long as ten days, the Release Agent may be removed by pressure rinsing with a high power pressure cleaner, or a soap and water solution, and scrubbed with a broom or by brush. Care should be taken not to remove all the release agent from the concrete, especially from grout lines and deeper indentations. To protect and help cure the concrete two coats of ColoredCrete High Gloss Clear Sealer are recommended.